



TYPE	W	t <sub>bl</sub>	H	H <sub>2</sub>	R <sub>(max)</sub>	Ød/D <sub>E</sub>	m**	a x a x h TYPE
	m	mm	m	m	m	mm	kg	m
RMV-S-60SRwAL	0,5	4	6		-	48; 60/145	20	0,3 x 0,3 x 1,0 F100/200
	1,0				0,6		21	
	1,5				1,3		21,3	
RMV-S-70SRwAL	0,5	4	7		-	48; 60/145	22,5	0,3 x 0,3 x 1,0 F100/200
	1,0				0,6		23,5	
	1,5				1,3		24,8	
RMV-S-80SRwAL	1,5	4	8			48; 60/145	45,1	0,3 x 0,3 x 1,5 F150/200
	2,0						45,9	
	2,5						46,7	
RMV-S-90SRwAL	1,5	4	9	2,0		48; 60/145	48,6	0,3 x 0,3 x 1,5 F150/200
	2,0						49,4	
	2,5						50,3	
RMV-S-100SRwAL	1,5	6	10		1,3	48; 60/180	52,1	0,3 x 0,3 x 1,5 F150/200
	2,0						52,9	
	2,5						53,8	
RMV-S-110SRwAL	1,5	6	11		1,3	48; 60/180	65,5	0,3 x 0,3 x 1,5 F150/200
	2,0						66,3	
	2,5						67,1	
RMV-S-120SRwAL	1,5	6	12		1,3	48; 60/180	69,1	0,3 x 0,3 x 1,5 F150/200
	2,0						69,9	
	2,5						70,7	

The technical data is listed for single-arm bracket posts:

- W=0.5m type AL bracket
- W=1.0m type AL-Y bracket
- W≥1.5m type AL-X bracket.

The maximum reach of AL-X brackets is W=3.5m.

Note: The number of diameter reductions depends on the post type.

\*\* - Data given for type AL-X and AL-Y two arm brackets.

STREET  
TUBULAR BRACKET TYPE

\* - Sizes listed for H≤7m posts



Our compliance with the European Community directives and harmonised standards has been certified and proven by the right to use the CE mark.